Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

RELIABILITY PREDICTION

Model : SP-75 Data:2001-04-04

Style	Part Type	Q'ty	λ_g	π_Q	λ_{eg}	%
9.1	Resistor-Film, Insulated (RL)	46	0.003700	10	1.702000	35.551
9.1	Resistor-Wirewound Power (RW)	2	0.008500	10	0.170000	3.551
9.1	Resistor-Film, Variable (RVC)	1	0.040000	10	0.400000	8.355
9.1	Resistor-Thermistor (RTH)	1	0.001400	10	0.014000	0.292
10.1	Capacitor-Metal, Plastic (CH)	16	0.000510	10	0.081600	1.704
10.1	Capacitor-Ceramic(Gen.) (CK)	13	0.001700	10	0.221000	4.616
10.1	Capacitor-Aluminum Dry (CE)	10	0.001300	10	0.130000	2.715
6.1	Diode-Gen. Purpose Analog	1	0.003600	8	0.028800	0.602
6.1	Diode-Switching	14	0.000940	8	0.105280	2.199
6.1	Diode-Fast Recovery Power Rectifier	4	0.023000	8	0.736000	15.374
6.1	Diode-Voltage Ref/Reg. (Avalanche & Zener)	5	0.003300	8	0.132000	2.757
6.1	Diode-Transient Suppressor/Varistor	1	0.002900	8	0.023200	0.485
6.10	Diode-Thyristor/SCR	1	0.002500	8	0.020000	0.418
6.4	Transistor-MOSFET	2	0.014000	8	0.224000	4.679
6.11	OPTO-isolator	2	0.027000	8	0.432000	9.024
6.11	OPTO-Emitter	1	0.000470	8	0.003760	0.079
5.1	Linear Microcircuits	3	0.009500	10	0.285000	5.953
11.1	Transformer Switching	1	0.000610	3	0.001830	0.038
11.2	Coil Fixed inductor or choke	3	0.000032	3	0.000288	0.006
17.1	Single Connections-Reflow solder	325	0.000069	1	0.022425	0.468
17.1	Fuses Clip-Clip Termination	2	0.000120	1	0.000240	0.005
22.1	Fuses	1	0.010000	1	0.010000	0.209
16.1	Plated Through Hole Circuit Boards	1	0.022000	2	0.044000	0.919
Total Failure rate:					4.787423	100%

- **Data Base: MIL-HDBK-217F ,Notice 2, Parts Count**
- **Env.: GB**

MTBF: 208880.64 **hrs**

Approved by: David Wang Compiled by: Kim Tseng .